CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

Please make one SOL8 tar file with the following packages:

.EcCsSubServer.pkg .EcCsMtMGTWY.pkg

.EcDl.pkg

.EcDlGUI.pkg

.EcDlWebAccess.pkg

.EcHg.pkg

.EcDmINTFCSVR.pkg

.EcDmDatabase.pkg

.EcDpAITWS.pkg .EcDpAtODL.pkg .EcDpPrPLNMGMTWS.pkg .EcDpPrQUESRVR.pkg

.EcOmDatabase.pkg .EcOmServer.pkg

.EcOmGUI.pkg

.EcPlDatabase.pkg .EcPlPLNMGMTWS.pkg .EcPlQUESRVR.pkg .EcPlODPRM.pkg

.EcNbGUI.pkg

.EcMsDbSupport.pkg

.EcMsDbSupport_SMC.pkg

.EcDbDDM.pkg

Please make one IRIX65 tar file with the following packages:

.EcDlDatabase.pkg

.EcDlQaUpdate.pkg

.EcDsSdSrvDb.pkg

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

.EcDsStArchive.pkg .EcDsStDatabase.pkg .EcDsStFtpCopy.pkg .EcDsStPullMonitor.pkg .EcDsStStaging.pkg

.EcInAPCSVR.pkg .EcInINTFCSVR.pkg

.EcNbDatabase.pkg

.EcNb.pkg

.EcOmFtpPush.pkg

.EcDbDDM.pkg

Please label this tar file Patch 7.00 System.05A

CSG

Please make a tar file from the REL7PTE baseline

SOL8

 $. \\ EcOmGUI.pkg$

.EcOmDatabase.pkg

Please label this tar file PATCH_7.00_SYSTEM.05A_SUPP.01

This delivers the following NCR for the first time in Patch 7.00 System.05A:

| NCR | PROJECT | Sev Stat | e Site | Description |
|--------------|---------|----------|--------|--|
| ECSed40276 C | PS_OM | 2 V | EDC | OMS Gui Should require the same orless work than DDIST GUI |
| ECSed40478 C | PS_OM | 2 V | GSFC | GSFC/SMC- OM GUI Resubmit not working – RequestID resubmit |
| ECSed40523 C | PS_OM | 2 V | GSFC | GSFC/SMC: OMS GUI infinite growth OM GUI Should Be Able To Handle Multiple |
| ECSed40353 C | PS_OM | 5 T | GSFC | Permissions Scenarios |
| ECSed40547 C | PS_OM | 2 V | PVC | System05B: The OMS GUI Aging Parameters page is not accessible |

The following NCRs have been delivered in Patch_7.00_SYSTEM.04B (See patch dependency list), but are also included in this patch:

| NCR | PROJECT | Sev State | Site | Description |
|----------------|---------|-----------|-------------|---|
| | | | | DBCC reported hard faults if dump tran when |
| ECSed38326 OPS | _DBDM | 3 T | PVC | running checkstorage |
| ECSed38592 OPS | DPool | 5 V | GSFC | GSFC/SMC - Add LocalGranuleID (FileID) column |

| CCR#04-0272 | R | ev: — | Originator: Dominick P. Iascone, Jr. | | |
|---|-------------|--------|---|--|--|
| Telephone: 301-925-1012 | TEMO | 5 A41. | Office: 3000X | | |
| Title of Change: Patch_7.00_SYSTEM.05A with SUPPLEMENTAL to DataPool | | | | | |
| ECSed39037 OPS_IDG, | 5 C | PVC | Implement SCP Media Type Through MTM Gtwy, Tool Needed to Update PlDataTypeMaster Tbl | | |
| ECSed39431 OPS_SEP | 5 V | LaRC | when Subscription Expires | | |
| ECSed39680 OPS_OM, | 3 C | EDF | Cleanup of FTP Pull Area in Synergy IV Quick Server failed to detect insufficient disk space | | |
| ECSed39738 OPS_OM | 2 V | VATC | when ftp push Calculate Checksum need a config parameter to | | |
| ECSed39931 RelB0_OM | 3 C | EDF | set to On/Off | | |
| ECSed39955 OPS_DBDM | 3 V | EDC | Sybase: Adjust filenames used by EcCoDbSyb_DumpDb DataPool: lastUpdate not updated by QA Update | | |
| ECSed40167 OPS_DPool, | 3 C | PVC | Utility | | |
| ECSed40209 OPS_OM | 2T | PVC | the active tape count doesn't get decremented when the granule is cancel | | |
| | <i>E\</i> / | LaDC | Ingest DB entry needed for new TES Level 2 data | | |
| ECSed40219 OPS_DBDM | 5 V | LaRC | GSFC/SMC: Rel 7 install problem with OMS ETE | | |
| ECSed40225 OPS_OM | 2T | GSFC | db transition script | | |
| | | | DPM GUI: Need to implement interface for DPL aging parameters, Assigned to = idey, Found: | | |
| ECSed40248 OPS_DPool, | 2C | EDF | 040413 | | |
| ECSed40249 OPS_OM | 2 V | PVC | OMS Order Email Information Incorrect | | |
| ECSed40266 OPS_OM, | 3 C | EDF | V0Gtwy fails to create orders in OMS db periodically | | |
| _ | | | Partially Transitioned Bands Found During | | |
| ECSed40277 OPS_DPool | 3 V | PVC | Transition Script Recovery Drop 7 Configured to Run 3 MTM Gtwys, EDC | | |
| ECSed40281 OPS_IDG | 2 V | EDC | uses 8 In OPS | | |
| ECSed40307 OPS_STMGT | 2 V | GSFC | Rel7_TSP: File size of metadata in pull dir does not match with email no | | |
| _ | | D) (O | 7.00_SYSTEM.01: Requests arriving in OMS from | | |
| ECSed40312 OPS_OM, | 2C | PVC | SSS without granules 7.00_SYSTEM.01: FtpPush stats updates are | | |
| ECSed40313 OPS OM, | 2 C | PVC | failing due to infinity field | | |
| ECSed40315 OPS_DBDM, | 2C | PVC | Improve performance of Staging Disk procs GSFC/SMC - Rel7 TS2: ECSGuest Orders arrive | | |
| ECSed40320 OPS_OM | 3 V | GSFC | with NORMAL Priority instead DumpDb/DumpTran jobs should NOT prevent each | | |
| ECSed40323 OPS_DBDM | 2 V | EDF | other | | |
| ECSed40324 OPS_OM, | 2C | EDF | In Addition to Active FTP, OMS Should Support Passive FTP | | |
| ECSed40325 OPS_OM | 3 V | EDF | OMS GUI displaying the wrong Completion Time for some request granules. | | |
| ECSed40332 OPS_DPool | 3 V | PVC | DPAD does not recognize certain DPIU race conditions as retries | | |
| ECSed40338 OPS_OM, | 2C | PVC | Order Manager cored while resuming archive p0drg01 | | |
| ECSed40340 OPS OM, | 3 C | EDF | OMS GUI: granule box present when granule failed and resubmit | | |
| ECSed40350 OPS_OM, | 2C | EDF | OM sends one no use and wrong email to web | | |
| | _ 0 | | 5 55do one no doo and mong ontail to wob | | |

CCR#04-0272 **Rev:** — **Originator:** Dominick P. Iascone, Jr. **Telephone:** 301-925-1012 Office: 3000X Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL users if orders are cancelled ProcIsGranReplacementNeeded treats ecsId ECSed40354 OPS DPool 3 T PVC match inconsistently ECSed40356 OPS DPool, webaccess: improve spatial search performance 3 C EDF FrontEnd missing support for ASTER GeoTiff NoReprojection conversion ECSed40362 OPS HEG 2 V PVC After ETE completed in two parts some Checksum ECSed40363 OPS DBDM, 2 C PVC types bad in SDSRV DB Database script EcOmRemoveOldReguests.ksh PVC should secure password ECSed40366 OPS OM, 2C Rel7 TS2P: First Gran Failed to Stage in Syn 4 ECSed40369 OPS OM 2 V GSFC Path EDC TS2: Release 7: DORRAN and PDS ECSed40370 OPS OM 1 T MTMGW not populating requestPriority field in ECSed40372 OPS IDG, 3 C EDF MSS OM doesn't immediately dispatch in-cache 2 C PVC ECSed40373 OPS OM, granules DPL storedproc shouldn't return L7 format1/2 3 V ECSed40375 OPS DPool EDF ESDT to OMS GSFC/SMC-Spatial Subscription Server is unable ECSed40378 OPS SSS 2T GSFC to keep up. ECSed40379 OPS Secure 2T GSFC GSFC/SMC: SSS PASSWORDS GSFC/SMC - Rel7 TS2: Order Manager Server ECSed40386 OPS OM 2 T GSFC Cored in TS2 Stmat Ftp Client Should give clients the option of ECSed40395 OPS STMGT 5 V EDF checking file size. Need Detailed Explanation for Operator ECSed40398 OPS OM 2 V EDC Interventions from OmServer DIDbArchiveAccessStat: script failed with insert ECSed40402 OPS DPool, 2C **EDF** EcCoModeCleanup script should be included in ECSed40403 OPS INSTALLATION 3 V LaRC EcCoMkDeliver OmServer stuck because of an auto-suspended 3 V request. ECSed40408 OPS OM EDF GSFC/SMC - SORCE polling having problems with ECSed40421 OPS STMGT 5 T **GSFC** connectivity ECSed40424 OPS SSS. 2 C Non-spatial gueries using SQS connection QA Update won't work if DPL Database built from ECSed40431 OPS DPool, 3 C EDF scratch Correct OMS DB iu file to deliver correct DB PVC ECSed40447 OPS_INSTALLATION 3 V objects DataPool Txn Log is Invalidated When 3 V EcDIRollupFwFtpLogs.pl Runs. ECSed40462 OPS DPool EDC Webaccess: old threads not die when appl is ECSed40465 OPS DPool 3 T EDF reloaded thru tomcat web mgr OM HUNG on Fetch OmSrPhysicalGranule fetch ECSed40493 OPS OM 2T PVC file list 2T ECSed40500 OPS OM PVC OM client libs cause core in MTMGW

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

DAAC INSTALLATION INSTRUCTIONS:

THESE INSTRUCTIONS ARE TO USED WHEN INSTALLING ANY MODE. IF YOU HAVE ANY QUESTIONS ABOUT INSTALLING SOMETHING THAT YOU HAVE ALREADY INSTALLED IN A PREVIOUSLY DELIVERED TE, THEN PLEASE CONTACT DERRICK CLARK OR WILLARD SELPH.

PATCH/TE DEPENDENCIES:

This must be installed on top of 7.00A. This Patch supercedes all of the following TEs/Patches:

TE_7.00_CSS.01 -- MTM is redelivered and must be installed from TE_7.00_System.03 **TE_7.00_OMS.01**. -- A new Database patch is delivered and the EcOmOrderManager server is replaced

TE 7.00 OMS.02. -- A new Database patch is delivered.

TE_7.00_SDSRV_DB_ETE_CHECKSUM.01A -- script is just re-delivered - no changes have been made.

TE_7.00_DPL.01 -- the QA Update scripts are re-delivered no new changes are included TE_7.00_STMGT.01A -- The Copy Server expect script is replaced in the TE 7.00 System.03 and must be installed

TE 7.00 INS REQ MGR.01 -- No changes were made to EcInReqMgr

TE_6A.08_SecureDist.02 -- The Ingest Expect scripts delivered in TE_7.00_System.03 are the same as these.

TE 7.00 SSS.01 – EcNbActionDriver.pl is re-delivered. No changes have been made.

Patch 7.00 SYSTEM.04B (May Patch)

NOTE: NCR 40194 will be sent as a TE in the future!

PRE-INSTALLATION:

- 1. Logon to the host where the EcOmFtpPush.pkg is installed (xxacgnn)
- 2. cd/usr/ecs/<MODE>/CUSTOM/cfg
- 3. cp EcOmFtpPassiveHosts.txt to EcOmFtpPassiveHosts.txt.orig (This will prevent the overwriting of this file that may have been modified.)

Create a staging area and move both Patch_7.00_SYSTEM.05A and Patch 7.00 SYSTEM.05A SUPP tar files to the same staging area directory.

Patch 7.00 SYSTEM.05A:

1. Using the Setup.ksh files for Patch_7.00_SYSTEM.05A in the <staging_area>/IRIX65 and <staging_area>/SOL8 untar the both the sun5.8 and irix65 tar files

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

- 2. As root, untar EcsAssist. (A new and improved from the 6A.08 version of the EcCoModeCleanup script is included in this delivery). **NOTE**: Do not delete the previous version of EcsAssist. Simply untar the new version over the old.
- 3. cd <staging area>/SOL8/CUSTOM
- 4. cp .selected packages .selected packages.orig

Patch 7.00 SYSTEM.05A SUPP:

- 5. Using the Setup.ksh files for Patch_7.00_SYSTEM.05A_SUPP in the <staging area>/SOL8 untar the sun5.8 tar files.
- 6. cd <staging area>/SOL8/CUSTOM
- 7. cp .selected packages.orig .selected packages
- 8. cd <staging area>/SOL8/CUSTOM/dbms
- 9. chmod -R 775 *
- 10. cd <staging area>/IRIX65/CUSTOM/dbms/
- 11. chmod -R 775 *
- 12. Bring down the HEG Frontend.
 - a. Log on to xxdpsnn as "cmshared".
 - b. Use the following command to determine if a "tomcat" process is running: /usr/ucb/ps -auxwww | grep front | grep < MODE>
 - c. If a "tomcat" process associated with the Front End process is running, login to the host where Web Access software resides and bring down tomcat using: /usr/ecs/<MODE>/CUSTOM/utilities/EcDlHEGFrontendControl <MODE> stop
 - d. Repeat steps "b, c". There should no longer be a "tomcat" process running in the mode. If there is, kill it from the command line.

INSTALLATION:

Logon to any SUN in the system and bring up E.A.S.I.

Install all packages. (Only packages in the tar file and in your .sitemap will be installed).

CONFIGURATION:

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

A. CSS

Create new configuration files for EcCsMtMGateway

1. Logon to the host where the package .EcCsMtMGTWY.pkg is installed (xxinsn).

- 2. Start the ECS Assistant Subsystem Manager
- 3. Select the MODE you wish to create configuration files for.
- 4. Double click "*CSS*"; then "*EcCsId*" and drill down to "*EcCsMtMGatewayApp*". A list of executables will be displayed.
- 5. Click the "*Configuration*" button to verify the settings. If any of the settings are not correct, please enter the correct value(s).
- 6. The following parameter was updated for EcCsMtMGateway:

| Parameter | Recommended Value | Definitions |
|-------------|-------------------|-------------------------------------|
| DBUSERNAME* | EcCsMtMGateway | Login for MtMGtwy server instances. |

^{*} These configuration parameters are not configurable and reside in the EcCsMtMGatewayMkcfg script.

- 7. Click the "**OK**" button to create configuration files for EcCsMtMGateway.
- 8. Change directory to "/usr/ecs/<MODE>/CUSTOM/cfg".
- 9. Execute the "diff" command for newly generated .CFG file(s) with .rgy before populating the registry with any newly generated .CFG file(s). The following command can be used:

For one file (this case) – "diff <file>.CFG <file>.CFG.rgy". Or, in this particular case, "diff EcCsMtMGateway_n.CFG EcCsMtMGateway n.CFG.rgy".

Where n represents the MtMGateway server instance number.

10. Move ("mv" command) file.CFG to file.CFG.rgy . Or, in this particular case, "mv EcCsMtMGateway_n.CFG EcCsMtMGateway_n.CFG.rgy".

Where n represents the MtMGateway server instance number.

11. Update Registry Database

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

a. Execute the command:

/tools/common/ea/EcCoPopulateRegistry MODE HostName ConfigFileName DbServerName DbUserName DbPassword DbName AttributeTreeName

The parameters are:

MODE - the mode that you are working in.

HostName – the name of the host (like g0acg01).

ConfigFileName – Give the fully qualified path name like /usr/ecs/<MODE>/CUSTOM/cfg/EcOmFtpPush.CFG.

DbServerName - SQL server name where Registry Database resides.

DbUserName – Registry database dbo name.

DbPassword – password dbo for the Registry Database.

DbName – EcCsRegistry <mode>. For OPS, use EcCsRegistry.

AttributeTreeName – the form is <mode> <release>.

12. Exit the ECS Assistant Subsystem Manager.

B. OMS

Create new configuration files for EcOmFtpPush

- 13. Logon to the host where the .EcOmFtpPush.pkg is installed (xxacgnn).
- 14. Start the ECS Assistant Subsystem Manager
- 15. Select the MODE you wish to create configuration files for.
- 16. Double click "**OMS**"; then "*EcOm*".
- 17. Click the "*Configuration*" button to verify the settings. If any of the settings are not correct, please enter the correct value(s).
- 18. The following parameters were added for EcOmFtpPush:

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

| Parameter | Recommended Value | Definitions | |
|------------------------|---|---|--|
| PassiveHosts | (DEFAULT = NULL) | This file contains a list of user accessible Passive FTP hosts. | |
| | /usr/ecs/ <mode>/CUSTOM/cfg/ EcOmFtpPassiveHosts.txt</mode> | | |
| CheckFtpDaemonFileSize | Default: OFF | Turns ON/OFF the FTP daemon reporting of transferred file size. | |

- a. The Parameter "**PassiveHosts**" will initially be set to a value of "**NULL**". The installer should change this to the recommended value displayed.
- b. The file "EcOmFtpPassiveHosts.txt" is copied to the directory "/usr/ecs/<MODE>/CUSTOM/cfg" during installation. Edit the EcOmFtpPassiveHosts.txt file adding a list of user accessible Passive FTP hosts. NOTE: The first line is just an example and can be removed.
- 19. Click the "**OK**" button to create configuration files for EcOmFtpPush.
- 20. Change directory to "/usr/ecs/<MODE>/CUSTOM/cfg".
 - a. cp EcOmFtpPassiveHosts.txt.orig EcOmFtpPassiveHosts.txt
 - b. Execute the "diff" command for newly generated .CFG file(s) with .rgy before populating the registry with any newly generated .CFG file(s). The following commands can be used:

For one file: diff file.CFG file.CFG.rgy

For multiple files (in c shell): foreach file (*.CFG), \(\pi \) echo \(\frac{\text{file}}{\text{sfile}} \) diff \(\frac{\text{file}}{\text{sfile}} \) end, \(\pi \)

- 21. Update Registry Database
 - Execute the command:
 /tools/common/ea/EcCoPopulateRegistry MODE HostName
 ConfigFileName DbServerName DbUserName DbPassword DbName

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr.

Telephone: 301-925-1012 **Office:** 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

AttributeTreeName

The parameters are:

MODE - the mode that you are working in.

HostName – the name of the host (like g0acg01).

ConfigFileName – Give the fully qualified path name like /usr/ecs/<MODE>/CUSTOM/cfg/EcOmFtpPush.CFG.

DbServerName - SQL server name where Registry Database resides.

DbUserName – Registry database dbo name.

DbPassword – password dbo for the Registry Database.

DbName – EcCsRegistry <mode>. For OPS, use EcCsRegistry.

AttributeTreeName – the form is <mode> <release>.

- 22. Move the changed.CFG files to .CFG.rgy files
 - a. For one file: mv <filename> <filename>.rgy

For multiple files (in c shell) foreach file (*.CFG) ↓ mv \$file \$file.rgy ↓ end ↓

Creating new configuration files for EcOmGui

- 23. Logon to the host where the .EcOmGUI.pkg is installed (xxdpsnn).
- 24. Start the ECS Assistant Subsystem Manager
- 25. Select the MODE you wish to create configuration files for.
- 26. Double click "**OMS**"; then drill down to "*EcOmOrderManagerApp*" (a list of executables will be displayed).
- 27. Select "EcOmGUI".

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

28. Click the "*Configuration*" button to verify the settings. If any of the settings are not correct, please enter the correct value(s).

29. The following parameters were added for EcOmGUI:

| Parameter | Recommended Value | Definitions |
|----------------|-------------------|---|
| ADMIN_OPERATOR | Admin (DEFAULT) | This allows operators within the password file to have admin priveledges. |

See "OMS GUI Admin Tools Features.doc" attachment for more information on the OMS GUI Admin Tools. <u>NOTE: NCR 40353 (OM Gui should be able to handle multiple permissions scenarios) delivers new functionality that is not ready for full implementation. To prevent implementation of the new functionality, do not create a "readWrite" password using the "EcCoCreatePassword" utility for the configured value.General Use of the Order Manager GUI is still available.</u>

DATABASE UPDATES:

NOTE: There is a dependency on the order in which the Database patches are applied. DataPool must be patched before the OMS Database is patched.

A. Add new login for EcCsMtMGateway.

This process entails adding the **EcCsMtMGateway** login and then adding the new user to the MSS and OMS databases.

- 1. Add EcCsMtMGateway login to the xxacgnn sybase server.
- a. Logon to the host where the package .EcOmDatabase.pkg is installed
- **b**. Change directory to /usr/ecs/TS2/CUSTOM/dbms/OMS/scripts
- c. View the file EcOmDbLogin, locating the line that contains "exec sp addlogin EcCsMtMGateway..."
- **d**. Perform the following sql commands to add EcCsMtMGateway login.

isql -U sa -S <xxacgnn Sybase server>

enter sa password

sp_addlogin EcCsMtMGateway, < characters between single quotes as noted in step 1.c.>, tempdb

go

2. Add EcCsMtMGateway user to the OMS database

Perform the following sql commands to add EcCsMtMGateway user to OMS database

isql -U oms_dbo -S <Sybase server> -D EcOmDb<_MODE>
enter oms dbo password

CCR#04-0272 **Rev:** — **Originator:** Dominick P. Iascone, Jr.

Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL sp adduser 'EcCsMtMGateway', 'EcCsMtMGateway', 'software'

go

3. Add **EcCsMtMGateway** user to the MSS database

Logon to the host where the EcMsDbSupport.pkg is installed (xxinsnn)

Change directory to

"/usr/ecs<MODE>/CUSTOM/dbms/MSS/ddm mss support/users"

Execute the following command:

EcMsActDbUser MODE USERNAME PASSWORD SERVER DBNAME

Where MODE is the mode your are installing

USERNAME is the dbo id for MSS database

PASSWORD is the dbo password

SERVER is the Sybase server for the MSS database

DBNAME is mss acct db< MODE>

B. STMGT Database Update:

If you have not previously installed TE 7.00 STMGT.01A then do the following:

Logon to the xxacgnn host and bring up EcsAssist Subsystem Manager Update the STMGT database with Patch 7046.

Patch 7044 fixes the following NCR:

NCR 40315 Fix performance problems for DsStSDAllocateDisk, DsStSDAllocateDisk and DsStSDAllocateDisk.

Patch 7046 Fixes the following NCRs: 40395, 40324, and 39738.

C. DPL Database Update

Logon to the host where the DPL database package is installed (xxacgnn) bring up ECS Assist Subsystem Manager and patch to 7104. The database should be currently patched to 7068.

The following database patches fix NCRs: 40462, 40354

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

Patch 7100: This patch adds the new column fileName to the DlGranuleAccess table and modifies the stored procedures ProcInsertFtpGranuleAccess and ProcInsertWebGranuleAccess to populate data for this new column

Patch 7102: This patch adds the new stored procedure ProcGetESDTSummaries and updates stored procedure ProcGetSpatialSummary to enhance performance for the spatial search.

The new stored procedure ProcDeleteOrderGranule was added to remove a single order only Granule. Also modified stored procedure ProcFindDeleteOrphanedBrowse and ProcGetUncleanOMSGranulesInfo.

Patch 7104: It adds indexes to DIFtpAccessLog, DIWebAccessLog, and DIGranuleAccess table.

Update ProcIsGrReplacementNeeded to add check of ecsId when checking for the same rangebeginningtime.

D. OMS Database Update:

Logon to the xxacsnn host and bring up EcsAssist Subsystem Manager Update the OMS database to the Patch **7309**. If you did not previously install TE 7.00 OMS.01 then you will be applying database patch 7117 as well.

Patch 7117 fixes the following NCRs:

NCR 40350 - Correct duplicate email notification

NCR 40325 - Change counts update to not update RequestGrStatus

NCR 40320 - Rel7_TS2:ECSGuest Orders arrive with NORMAL Priority instead LOW in Order Manager GUI

NCR 40370 - TS2: Release 7: DORRAN and PDS

Patch 7123 fixes the following NCRs:

NCR 40194 - Fix for counts update - OmUpdateOverallStats

NCR 40312 - Contention enhancement to OmInsertGranule

Patch 7125: This patch contains a fix for the following problem:

NCR 40194 - Modified OmUpdateOverallStats stored procedure to provide a fix for counts update.

Patch 7300: This patch contains modifications to the EcOmRemoveOldRequest, OmSetQueueState, OmInsertGranule, and OmUpdateGranStatus stored procedures.

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

Patch 7302: This patch contains modifications to OmUpdateOverallStats and OmInsertGranule stored procedures. Also adds new ExplanationCodes to the

OmExplanation table.

Patch 7304: This patch contains a fixes for the following problems:

NCR 40398 - Modify OmSuspResumeRequest to use correct Explanation Code when suspending the request.

NCR 39680 - create new stored procedure to delete the granule in DPL. If deleted, need to remove the corresponding files from DPL SAN.

Patch 7305: This patch contains a fix for the following problem:

NCR 40194 - Modified OmUpdateOverallStats stored procedure to provide a fix for counts update.

Patch 7309: Fixes NCRs ECSed40546 and ECSed40478.

E. PDPS Database Update (LaRC Only)

Logon to the l0sps03 host.

Bring up EcsAssist Subsystem Manager Update the PDPS database to Patch 7000.

Patch 7000 adds a new column subscriptionExpDate to the PlDataTypeMaster table

F. DDM Administration Script Updates

We recommend the following script be executed to insure database administration works properly during system usage.

Use the following table as a guide.

| EDC | GSFC | LARC | NSIDC |
|---------|---------------|---------|---------|
| e0acg11 | g0acg01 | 10acg02 | n0acg01 |
| e0acs11 | g0acs11 | 10acs03 | 10acs04 |
| e0icg11 | g0icg01 | 10sps03 | |
| e0sps04 | m0mss16 (SMC) | | |

Logon to each host listed for your DAAC as cm<MODE> and execute the following instructions:

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch_7.00_SYSTEM.05A with SUPPLEMENTAL Change directory to "/usr/ecs/<MODE>/CUSTOM/dbms/COM/DBAdmin"

Execute the following script for every Sybase server:

EcCoDbSyb CreateDbaProcs <Sybase srvr>

You will be prompted for password.

Enter the "sa" password

G. End-To-End Checksum Transistion Script Updates:

The SDSRV End-To-End ChecksumTransition Scripts (including the new one for GSFC) and a new version of the OMS End-To-End Checksum Transition script are delivered in this delivery.

For modes that have not been transitioned use the instructions in the Release 7 Release Notes to complete the End-To-End Checksum Transition activities. For modes where the ETE Transition has been completed nothing new is required.

To run the new EcOmETEtransition.ksh enter the following:

- 1. Logon to the host where .EcOmDatabase.pkg is installed.
- 2. setenv SERVER <xxacgnn srvr>
- 3. EcOmETEtransition.ksh < MODE>

The script will prompt you for the database user name -- enter the dbo name The script will then prompt you for the dbo password

This script only drops and re-creates the OmGetSdsrvFileInfo and OmValidateGranules stored procedures -- This must be done AFTER the SDSRV End-to-End is completed.

POST INSTALLATION:

If you did not bring down the entire system, do the following:

- 1. Logon to the xxacsnn host and start the EcOmOrderManager and the EcCsSubServer
- 2. Logon to the xxinsnn host and start the V0ToEcsGateway and all instances of the EcCsMtMGateway
- 3. Logon to the xxacgnn host and xxdrgnn hosts and start all of the STMGT Servers
- 4. Restart HEG Frontend tool using the following instructions:
 - a. Log on to xxdpsnn as "cmshared".

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch 7.00 SYSTEM.05A with SUPPLEMENTAL

- b. Use the following command to determine if a "tomcat" process is running: /usr/ucb/ps -auxwww | grep front | grep < MODE>
- c. If a "tomcat" process associated with the Front End process is running, login to the host where Web Access software resides and bring down tomcat using: /usr/ecs/<MODE>/CUSTOM/utilities/EcDlHEGFrontendControl <MODE> stop
- d. Repeat steps "b, c". There should no longer be a "tomcat" process running in the mode. If there is, kill it from the command line.
- e. Start the tomcat process, associated with the Front End process, by running: /usr/ecs/<MODE>/CUSTOM/utilities/EcDlHEGFrontendControl <MODE> start
- f. Logon to the xxdps01 host and bounce the iPlanet instance for the OMS & SSS GUIs.

If your DAAC has any Data Providers that use secure copy and want to use the passphrase instead of the password then do the following:

- g. Logon to the xxacsnn host where the EcInGUI is installed.
- h. Bring up the Ingest GUI and update the Ftp Password for the specific data provided to the passphrase instead of the password.
- e. Reload DPL Web access application for the mode you have installed
 - a. Access the Tomcat Manager Page using the follow example URL: http://xxdpsnn[domain name]:[Port number used by tomcat manager]/index.jsp
 - b. Click "Tomcat Manager" within the Administration Box. You will be prompted for the userid and password.
 - c. The "Tomcat Web Application Manager" page is displayed
 - d. Click the "Reload" button for the mode that was installed listed in the Commands column. The Web Access application for the selected mode will be refreshed.

THESE INSTRUCTIONS ARE TO BE USED WHEN INSTALLING ANY MODE. IF YOU HAVE ANY QUESTIONS ABOUT INSTALLING SOMETHING THAT YOU HAVE ALREADY INSTALLED IN A PREVIOUSLY DELIVERED TE, THEN PLEASE CONTACT DERRICK CLARK OR WILLARD SELPH.

CCR#04-0272 Rev: — Originator: Dominick P. Iascone, Jr. Telephone: 301-925-1012 Office: 3000X

Title of Change: Patch_7.00_SYSTEM.05A with SUPPLEMENTAL